Miele



Miele Professional Laundry & Dishwashing **Product Range**



About Gillman's

Gillman's is a family run business established in Gloucester by John and Erika Patricia Gillman in 1969, originally as a service and repair company.

Robert, the eldest of their 3 children joined the company in 1970 followed by his sister Annabelle and brother Adrian. They are now the current owners/directors of the business.

Since then the business has expanded and diversified into many sectors of the electrical and gas appliance industry, covering national distribution, retail and service of both domestic and commercial appliances, and now employ in excess of 150 people.

Gillman's was one of the founding members of the Miele Partnership and work closely with Miele to provide the highest quality service. The installation team have been fully trained by Miele, which ensures that all the equipment

supplied by them is installed to Miele's specification and current legislation.

The company operates a large retail showroom in Gloucester, supported by an aftersales team. A warehousing and distribution centre is based in Tewkesbury. They pride ourselves on product knowledge and customer service and are proud to be independent.

Gillman's will discuss your requirements with you and then advise the most suitable layout for your laundry or kitchen. They will give you a detailed quotation for all the necessary work, including a professional plan of the installation most suitable for your application.



66 Our site has always used Miele machines and we would never change that.





References





Client: The Chace Care Home



The Chace Care Group speeds up laundry processes and bolsters infection control with Miele

Providing residents with a caring, hygienic and peaceful environment is a priority for The Chace Care Home. Owned by care provider The Chace Care Group, the home has been run by two generations of Reeley family for over thirty-five years. Taking a family approach to care, they prioritise meeting strict care and hygiene guidelines not just for health and safety reasons, but also to ensure that they're providing the best standards of care for residents.

Every day the dedicated laundry staff take care of the issues faced by a typical care home. The Chace recognised the need for laundry equipment with quick wash cycles that are also highly effective at killing any traces of infection. Cleaning items in a shorter timeframe helps to prevent the spread of infection and ensure compliance with Care Quality Commission (CQC) guidelines relating to hygiene.

The home's previous machines were also noisy, which slowed laundry processes. As bedrooms are located to the laundry room, staff couldn't use the machines or tumble dryers at night otherwise residents would be disturbed. This meant that items would often have to wait until the next

day before being cleaned, increasing the potential risk of infection.

Looking to upgrade its equipment, Gillman's, a longstanding partner of Miele advised The Chace that Miele machines would be able to deliver on its speed, noise and infection control requirements. Familiar with Miele, The Chace agreed that this was the brand that could solve its laundry challenges.

Domestic staff at The Chace now have more time to focus on their everyday tasks thanks to quicker laundry processes, and this is having a positive impact on residents.

The Chace selected two Miele PW 5105 washing machines and two PT 8303 tumble dryers. Gillman's installed the new machines in a day and a full demonstration of how to use the new equipment was given to staff so that they could use the full functionality on offer by the machines

and understand which programmes to use on items that posed an infection risk. Thanks to Gillman's' fast work, The Chace's laundry practices were not impacted so there was no need to outsource its washing while the implementation was taking place.

Domestic staff at The Chace now have more time to focus on their everyday tasks thanks to quicker laundry processes, and this is having a positive impact on residents. The new laundry processes contribute to helping The Chace meet stringent CQC guidelines and the home's own standards for hygiene can now also be met more effectively.

Anthony Reeley, managing director at

The Chace Care Home says: "When my family opened the business, they worked hard to build a reputation in the area as a trustworthy and respectable care home. Having had over 35 successful years since then, I'm keen for this to continue and ensure that our residents continue to receive excellent standards of care. Our cleaning and hygiene procedures are part of this and that's why we installed new Miele machines that can keep the standards high."

Client: Prior's Court School



66

Now we have so much more space which makes such a difference. The barrier washer-extractor machines provide us with peace of mind and we now have optimal infection control.

Prior's Court School for young people with autism invests in Miele Professional for laundry upgrade.

Prior's Court is an independent special school for young people with autism.

They accommodate students aged between five and 19 and also provide support for families of the children. Their primary focus is to build independence and social skills in their students.

Before the recent laundry installation,
Prior's Court already had a good
relationship with the esteemed
German brand, having used Miele
Professional machines on site for over
15 years. Colin Seatter from Prior's
Court explains that they 'invest in
Miele Professional machines because
they are so good. They really are the
best that money can buy!'

Having previously had two small laundries installed with Miele Professional Little Giants, the team at Prior's Court decided that they wanted to upgrade the laundry facilities. After considering the various options that Miele Professional offer when it comes to an on premise laundry solution, they decided to invest in barrier washer-extractors.

Barrier laundry was the best option for the school being particularly concerned with infection control. Introducing enforced control measures within the laundry made complete sense, to ensure the highest standard of linen hygiene throughout the entire process, with the additional benefit of increased productivity, always an issue of paramount importance when dealing with children who have special needs.

An old unused changing room on site was repurposed to become a brand new laundry room and was fitted with three barrier washerextractor machines (2 x 16kg and 1 x 20 kg) and three commercial tumble dryers.

Having decided to invest in a whole new on premise laundry, Prior's Court turned to Gillman's to conduct the installation of the Miele Professional barrier washer-extractor machines. Gillman's spent a year planning and executing the project and were able to carry out the whole process from design to installation and service. They also gave the cleaning team at Prior's Court advice on all aspects of a best laundry practice. Gillman's were delighted to be involved in the project with Prior's Court School.

Speaking about how the recent installation has benefited the school,

Colin Seatter explained: 'The new machines have been fully operational for 4 months now and the whole laundry process runs 100% better than it did before – there is no doubt about it! The cleaning staff absolutely love the new laundry. Now we have so much more space which makes such a difference. The barrier washer-extractor machines provide us with peace of mind and we now have optimal infection control.

that we have been able to improve efficiency. The laundry is staffed between 7am and 3pm. Laundry is collected in the evenings and is returned back to the children the next day. We now have plans to use the old laundry as a training site for the children; the machines will remain operational so they will be able to learn how to use them which helps teach essential life skills.'

The new installation has also meant

When asked if he would recommend the German brand, Colin commented: 'Of course we would recommend Miele Professional. Our site has always used Miele machines and we would never change that.'

Partnered with Miele

What does a Miele Approved Partner mean?

In 2001, Miele established the Miele Professional Partnership choosing to sell laundry and dishwashing products to customers through a network of approved Partners. The reasons for this are to provide the customer with a fast, local solution.

Gillman's is an approved Partner, meaning that they undergo Miele product and service training and they are able to sell, install, commission and service any Miele Professional product.

What are the benefits to Gillman's customers?

By Miele selling in this way, our customers are able to buy the quality of Miele products, with the reassurance that they will receive the personal support and knowledge from Gillman's.



This is to certify that



is an

Approved Miele Sales & Service **Partner**

Authorised by Sam Bailey



Product range contents

08-13

11-32 KG

Tumble Dryers Washer-Extractors LITTLE GIANTS LITTLE GIANTS 16 PT 5137 WP PW 6055 Vario PW 6065 Vario PT 7136 Vario PT 7137 WF PW 6080 Vario PWT 6089 Vario PT 7186 Vario PW 5105 Vario PT 8203 WP 10-13 KG

12-15 KG

13-16 KG

PT 8337 WF

16-20 KG

20-25 KG

32-40 KG

PW 413 Mopstar 130 BARRIER WASHERS 13

PW 6243

20-25

Ironers

ROTARY HM 16-83 **FLATWORK** PM 1217 PM 1421 PM 1621 PM 1625 PM 1630

PM 1635

PM 1825

PM 1835

26-30

Dishwashers

PROFILINE PG 8080 PG 8080 U PG 8082 SCi PG 8083 SCVi **PROFESSIONAL** PG 8058 - Brilliant

PG 8172 - Performance





Washer-Extractors

Miele Professional's laundry technology guarantees hygienically clean laundry.

Patented Honeycomb Drum

Ensures the gentle care of fabrics combined with first-class cleaning and drying performance.

Award winning Environmental Technology

All Miele Professional washing machines have recently been approved for inclusion on the Water Technology List for improved water efficiency.

Highest G-Force

A G-Force of up to 526 occurs during extraction, reducing drying times, energy costs and extending the life of the garment.

Large range of capacities catering for a wide market

- 5.5 to 32 kg drum volumes for washer-extractors
- Specially designed machines for washing mops and cloths
- Barrier machines for care homes and hospitals

WRAS Approved

Washing machines are compliant with machinery guidelines and WRAS approved for reassurance.

Barrier Washers

Miele Professional barrier machines offer optimum physical separation between unclean and clean sides in care homes and hospitals. preventing contamination of laundry.

LITTLE GIANTS

PW 5062 PW 6055 Vario PW 6065 Vario PW 5064 Mopstar 60

8-10 KG

PW 6080 Vario PWT 6089 Vario PW 5105 Vario

PW 811 PW 413

11-32 KG

PW 413 Mopstar 130 PW 814

PW 418 PW 818 PW 6241 PW 6321

BARRIER WASHERS

PW 6163 PW 6243 PW 6323

Control Panels

The variety of Miele interface controls for our products are all designed to be easy to use and ensure maximum efficiency during the cleaning cycle.







Profitronic L Vario:

left display to enable the user to manage their time efficiently. Wide range of standard programme ll as a number of special programmes such as table linen, pillows and outerwear and reproofin eature of four short cut keys for most popular programmes on the Plus version.

Profitronic M:

unction selector and user navigation scre n. 199 programme slots. ctor or 6 short cut buttons. Freely programmable programme

Profitronic D:

Profitronic D controls provide programmes catering for the entire spectrum of laundry care requirements. A text display and 6 direct-access buttons facilitate ease of use and fast programme selection. The most frequently used programmes are assigned to buttons 1-6 and are ac of a single button. Further programmes are accessed by pressing and holding bu parameters such as temperature and spin speed can be selected manually before the start of eac programme. Similarly, current load sizes can be entered to reduce water, energy and de consumption accordingly.

Little Giants - 5.5-6.5 KG







8-10 KG Washer-Extractors

module slot

module slot













Available in white or stainless steel*

*Drain pump only



Special Programmes for mop head washing





100 mg								
Product Code	PW 5062	PW 6055 Vario	PW 6065 Vario	PW 5064 Mopstar 60	PW 6080 Vario	PWT 6089 Vario		PW 5105 Vario
						Washer - PWT 6089	Dryer - PT 7189	
Capacity (kg)	6.5	5.5	6.5	6.5	8	8	8	10
Dimensions: H/W/D (mm)	850/595/725	850/595/725	850/595/725	850/595/725	1020/700/727	1920/692/763	1920/692/763	1020/700/827
Net Weight (kg)	109	106	109	105	140	240	180	148
Heating	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
Controls	Profiline B Plus	Profitronic L Vario	Profitronic L Vario	Profiline MOP	Profitronic L Vario	Profitronic L Vario	Profitronic L Vario	Profitronic L Vario
Spin Speed (rpm)	1400	1400	1400	1400	1300	1300	-	1100
G Factor	526	526	526	526	520	520	-	370
Residual Moisture (%)	49	49	49	25	49	49	-	54
Drainage	Drain Pump	Drain Pump	Drain Pump or Dump Valve	Dump Valve	Drain Pump or Dump Valve	Drain Pump	-	Drain Pump or Dump Valve
Electric Requirements: 230V	•	•	•	•	•	•	•	•
400V	-	•	•	-	•	•	•	•
Other Comments	Stackable	Stackable	Stackable	Stackable	Communication	Communication	Communication	Communication

WASHER-EXTRACTORS





PW 811



11-32 KG Washer-Extractors



PW 413 Mopstar 130 PW 814

14-16

324

1075

1452/924/850 (757*)

Electric or steam

Profitronic M

Dump Valve









PW 6241







16-32 KG Barrier Washer-Extractors



Capacity (kg)
Dimensions: H/W/D (mm)
Net Weight (kg)
Heating

Controls Spin Speed (rpm) G Factor

Product Code

Residual Moisture (%) Drainage

Electric Requirements: 230V

Other Comments

400V

11-12	13-14
1352/799/940 (827*)	1352/799/1010 (897*)
257	266
Electric or steam	Electric
Profitronic M	Profitronic D
1150	1025
460	360
45	50
Dump Valve	Dump Valve

PW 413

Communication module slot

* Depth by removing panels and protruding parts

Communication module slot

Data shown is for the

electric versions

1352/799/1010 (897*) Electric Profitronic D Mop

> Communication module slot Special programmes for

13-14

mop head washing * Depth by removing panels and protruding parts

* Depth by removing panels and protruding parts

Communication module slot Data shown is for the electric versions * Depth by removing panels

* Depth by removing panels and protruding parts

PW 418 PW 818 18-20 18-20 1452/924/950 (857*) 1452/924/950 (857*) Electric or steam Electric Profitronic D Profitronic M 1075 950 Dump Valve Dump Valve

Communication module slot Communication module slot Data shown is for the electric versions

and protruding parts * Depth by removing panels and protruding parts

1640/1085/1265 Electric, Gas or Steam Profitronic M 1100 Dump Valve

Data shown is for the electric versions

Data shown is for the

electric versions

PW 6321 PW 6163 PW 6243 PW 6323 1718/1605/1070 1640/1085/1272 1718/1153/1070 1718/1384/1070 630 820 860 Electric, Gas or Steam Electric Electric Electric Profitronic M Profitronic M Profitronic M Profitronic M 1000 1025 975 360 400 50 50 Dump Valve Dump Valve Dump Valve Dump Valve

Tumble Dryers

Miele Professional's laundry technology guarantees hygienically clean laundry.

Patented Honeycomb Drum

Ensures the gentle care of fabrics combined with first-class cleaning and drying performance.

Residual Moisture Control Dryers

Accurate sensors that measure moisture in the garments to reduce drying times and lower energy costs.

Award winning Environmental Technology

New and innovative Heat Pump dryers and H₂O dryers reduce energy costs by over 50%.

Highest G-Force

A G-Force of up to 526 occurs during extraction, reducing drying times, energy costs and extending the life of the garment.

Large range of capacities catering for a wide market

A capacity range of 6.5 to 40 kg drum volumes for our dryers meets the needs of businesses large and small.

H₂O Dryers

The H₂O dryer can be put to use wherever water is heated. This can take the form of an on-site cogeneration plant, district heating or alternative sources of energy where hot water is a by-product.



Little Giants - 6.5KG










12-15 KG







Condenser model



Heat Pump model



Condenser model



Vented model



Heat Pump model





*1:25 - 1:20kg



Blue

Vented





Product Code
Capacity (kg)
Dimensions: H/W/D (mm)
Net Weight (kg)
Heating
Controls
Electric Requirements: 230V
400V

Other Comments

ode	Р
ty (kg)	6.5
(mm)	85
nt (kg)	60
eating	Ele
ntrols	Pro
230V	•
400V	-

Pī	T 5135 C	PT 5137 WP	PT 7135 C Vario	PT 7136 Vario	PT 7137 WP	PT 7186 Vario	PT 8203 WP	PT 8253	PT 8257*	PT 8257 WP	PT 8301	PT 8303
6.5	5	6.5	6.5	6.5	6.5	8	8-10*	10-13	10-13	10-13*	12-15	12-15
850	50/595/710	850/595/727	850/595/710	850/595/710	850/595/727	1020/700/763	1800/711/1075	1400/906/852	1400/906/852	1400/906/1218	1800/711/1089	1800/711/10
60)	77	61	58	77 (79 stainless steel)	77	202	149	149	148	139(EL) /145(G)	139(EL) /145(
Ele	ectric	Electric	Electric	Electric	Electric	Electric, Gas	Electric	Electric or Gas	Electric or Gas	Electric	Electric or Gas	Electric or Ga
Pro	rofiline L	Profiline L	Profitronic L Vario	Profitronic L Vario	Profitronic L Vario	Profitronic L Vario	Profitronic B Plus	Profitronic B Plus	Profitronic M	Profitronic M	Profitronic B	Profitronic B I
•		•	•	•	•	•	-	• (Gas)	• (Gas)	-	-	-
-		-	-	•	-	•	•	• (Electric)	• (Electric)	•	•	•
	ailable in white ackable	Available in white Stackable	Available in white or stainless steel Stackable	Available in white or stainless steel Stackable	Available in white or stainless steel Stackable	Vented model Available in blue or	Heat Pump integrated	Communication module slot	Communication module slot	Heat-Pump unit dimensions (H/W/D):1370/906/433	Vented model COP models available	Vented model

stainless steel

*Image shown

Blue (Gas only)/

Stainless Steel Vented

* 1:25 - 1:20kg

13-16 KG **TUMBLE DRYERS**



COMPLIANT WITH MACHINERY GUIDELINE SOMMERCE SOMM



COMPLIANT WITH MACHINERY OUIDELINE SOURCES SOURCE SOU

PT 8803

1640/1206/1384

Profitronic B Plus

32-40











20-25 KG







Capacity (kg)
Dimensions: H/W/D (mm)
Net Weight (kg)
Heating
Controls
Electric Requirements: 230V

Product Code

Other Comments

PT 8333	PT 8337*
13-16	13-16
1400/906/1035	1400/906/10

13-16 1400/906/1035 166 (EL), 169 (G, HW) Electric, Gas or HW Profitronic M

Communication module slot Vented with AirRecycling system HW (Hot Water) version for

 (Gas) • (Electric)

H₂O model

166 (EL), 169 (G, HW) Electric, Gas or HW

*Image shown

Profitronic B Plus • (Gas) • (Electric)

> module slot Vented with AirRecycling system HW (Hot Water) version for H₂O model

Communication Heat-Pump unit dimensions (H/W/D):1370/906/433

PT 8337 WP

1400/906/1401

13-16*

164

Electric

Profitronic M

* 1:25 - 1:20kg

Communication module slot Vented with AirRecycling system HW (Hot Water) version for H₂O model

PT 8403

1400/906/1164

Profitronic B Plus

192 (EL), 190 (G), 217 (S, HW)

Electric, Gas, Steam or HW

16-20

Communication module slot Vented with AirRecycling system HW (Hot Water) version for H₂O model

PT 8407*

1400/906/1164

Profitronic M

192 (EL), 190 (G), 217 (S, HW)

Electric, Gas, Steam or HW

16-20

•

*Image shown

PT 8503	PT 8507
20-25	20-25
1640/1206/1018	1640/1206/1018
239 (EL), 240 (G), 265 (S, HW)	239 (EL), 240 (G), 265 (S, HW)
Electric, Gas, Steam or HW	Electric, Gas, Steam or HW
Profitronic B Plus	Profitronic M
-	-
•	•

HW (Hot Water) version for H₂O model

Communication module slot HW (Hot Water) version for H₂O model Communication module slot HW (Hot Water) version for H₂O model

286 (EL), 287(G), 318 (S,HW)

Electric, Gas, Steam or HW

Communication module slot HW (Hot Water) version for H₂O model

*Image shown

PT 8807*

1640/1206/1384

Profitronic M

287 (EL,G), 318 (S,HW)

Electric, Gas, Steam or HW

32-40

Commercial Ironers

Smooth, crease-free finish

Optimum laundry finish

Miele rotary ironers are just the machines for a perfect finish on workwear and table linen: simple, fast and economical. In hotels and restaurants, perfectly laundered textiles help keep up appearances. Alongside guaranteeing a perfect finish, rotary ironers are above all simple and safe to use. Roller speed is infinitely selected temperatures and roller speeds are all selectable using a rotary selector. Roller rotation can be stopped at any time by pressing the footswitch. The ARAMID cloth and the aluminium trough ensure efficient results.

The patented automatic finger guard stops the roller in its tracks and retracts the heater plate in the event that anything enters the gap between the roller and the trough. During power failures, the heater plate can be released easily to remove trapped items.

High Performance

Our high-performance flatwork ironers are able to process more than 200 kg of laundry per hour, equating to more than a tonne of laundry per day. These large ironers can be controlled and monitored from their central display, making them safe and easy to use. Contact pressure, and can be saved with password protected user levels. The display also shows cleaning and waxing reminders when due.

Model designations PM 16 and PM 18 are available with electric, gas and steam heating and the touch display shows all the machine parameters at a single glance, allowing the ironer to adapt fast to everyday working conditions.





Flatwork Ironers





Steam Facility

Return Feed











Return feed (new machines, electric model only)



Return feed (new machines, electric model only)

Product Code	HM 16-80	HM 16-83	PM 1210	PM 1214	PM 1217	PM 1318
Roller diameter (mm)	160	160	210	210	250	300
Roller width (mm)	830	830	1000	1400	1660	1750
Heater plate	Electric	Electric	Electric	Electric	Electric	Electric or Gas
Throughput according to DIN 11902 (kg/h):						
Residual moisture 15%			30			
Residual moisture 20%	13	15				
Residual moisture 25%				33	60	75(EL)/53.7 (G)
Electric Requirements: 230V	•	•	•	-	-	-
400V	-	-	•	•	•	•
External dimensions H/W/D (mm)	959/985/380	960/1050/380	1032/1579/476	1032/1979/650	1110/2238/650	1318/2576/1150
Other Comments	Folding frame	Return Feed	Return Feed	Return Feed	Return Feed and Through Feed	Through feed (option of return feed module for existing machines)

300 365
1750 1750
Electric or Gas Electric or Gas

75(EL)/53.7 (G) 90
•
1318/2576/1150
Through feed (option of return feed module for existing machines)

Through feed (option of return feed module for existing machines)

PM 1418

Flatwork Ironers











Roller diameter (mm)
Roller width (mm)
Heater plate
Throughput according to DIN 11902 (kg/h):
Residual moisture 25%
Electric Requirements: 230V
400V
External dimensions H/W/D (mm)

Other Comments

Product Code

PM 1421	PM 1621	PM 1625	PM 1630	PM 1635	PM 1825	PM 1830	PM 1835
365	585	585	585	585	790	790	790
2040	2100	2500	3000	3500	2500	3000	3500
Electric or Gas	Electric or Gas	Electric, Gas or Steam	Electric, Gas or Steam	Electric, Gas or Steam	Electric, Gas, Steam	Electric, Gas or Steam	Gas or Steam
96(EL)/70 (G)	115 (E/G)	130(EL,G)/135(S)	145(EL,G)/165(S)	160(EL,G)/190(S)	165 (EL,G,S)	200 (EL,G,S)	235 (G/S)
-	-	-	-	-	-	-	-
•	•	•	•	•	•	•	•
1318/2866/1150	1970/3290/1840	1970/3690/1840	1970/4190/1840	1970/4690/1840	1970/3690/2044	1970/4190/2044	1970/4690/2044

Through feed (option of return feed module for existing machines)
Return feed (new machines, electric model only)

Dishwashers

Miele Professional's range of commercial dishwashers meet the needs of the most stringent commercial and care environments

Efficient

Extremely short programme cycles capable of completing full freshwater wash cycles in as little as 5 minutes.

Environmentally friendly

Intelligent programmes can be customised to optimise energy and water consumption.

High performance

Miele's unique freshwater system operates with fresh water in every cleaning cycle achieving high hygienic standards and low energy usage. Hygienic cleanliness is achieved with high rinse temperatures in excess of 80 degrees.

Dependable

All machines are compliant with machinery guidelines and the freshwater dishwashers are WRAS approved for reassurance.

Recommended

Our dishwashers are recommended by Riedel as the perfect machines to wash their delicate glassware.

Key Features

Profiline:

dishwashers have

short cycle times,

performance and

making them perfect

showrooms and ever

Professional:



The **PG 8055 SPEED** and PG 8056 SPEEDPlus

are the fastest commercial dishwashers using the fresh water circulation system and are ideal for hotels, restaurants, clubs and schools. With its 456 plates an hour.

BRILLIANT

The PG 8058 BRILLIANT

need to polish glassware a RO water system. This feature combined with shortest wash cycle of just the fresh water circulation 5 minutes it can wash up to system are unique to Miele Professional.

HYGIENE

PG 8059 HYGIENE

its uncompromisina exception making hospitals, nursing homes and nursery

Tank:



UNIVERSAL



Miele Professional Tank system dishwashers have fast cycle times with a maximum theoretical throughput of up to 3234 glasses or 1296 plates per hour, making them perfect for the demands placed on hotels, restaurants, pubs and bars.

PROFILINE

PG 8080 PG 8080 U PG 8081 i PG 8082 SCi PG 8083 SCVi

PROFESSIONAL

PG 8055 - Speed PG 8056 - Speed Plus PG 8058 - Brilliant

PG 8059 - Hygiene

TANK

PG 8164 - BrilliantCompact PG 8165 - UniversalCompact

PG 8166 - Universal PG 8172 - Performance

ProfiLine Dishwashers



Professional Dishwashers







Product Code

DISHWASHERS

















Dimensions: H/W/D (mm)
Net Weight (kg)
Туре
Dishwashing system
Shortest programme cycle (mins)
Plate capacity (plates/h)
Dishwashing programmes
Final rinse temperature
Door lock

PG 8080	PG 8080 U	PG 8081 i	PG 8082 SCi	PG 8083 SCVi	PG 8055	PG 8056	PG 8058	PG 8059	
845/598/600 62	805/598/570 54	805/598/570 55	845/598/570 56	845/598/570 56	835/600/600 63	835/600/600 63	835/600/600 63	835/600/600 63	
Freestanding unit	Built under unit without lid	Integrated unit	Integrated unit	Fully integrated	Freestanding unit	Freestanding unit or built under (PG 8056U)	Freestanding unit	Freestanding unit	RONE
Freshwater system	Freshwater system	Freshwater system	Freshwater system	Freshwater system	Freshwater system	Freshwater system	Freshwater system	Freshwater system	:RS
18 (32A model)	18 (32A model)	18	19	19	9	6 at 55°C	6 at 55°C	6 at 85°C	
13	13	13	14	14	200	380	380	380	
9	9	9	9	9	9	11	11	11	
75°C	75°C	75°C	75°C	75°C	70°C	70°C	85°C	85°C	
Auto Open	Auto Open	Auto Open	Auto Open	Auto Open	Easy Open	Easy Open	Auto Open	Auto Open	

Tank Dishwashers

BRILLIANTcompact

PG 8164

Tank system

725(760)/460/617

Freestanding/built under

1600 glasses or 600 plates

3 + 4 additional programmes









Dimensions: H/W/D (mm) Dishwashing system Baskets/hr







PG 8165

Tank system

725(760)/600/617

Freestanding/built under

3234 glasses or 882 plates

3 + 4 additional programmes





	U
PG 8166	PG 8172
820(855)/600/617	1515 (1995) /635/750
Freestanding/built under	Freestanding/Throughfeed
Tank system	Tank system
55	50
1188 plates	1296 plates
66	72
3 + 4 additional programmes	3 + additional programmes

PERFORMANCE

_ Miele History & Innovation

Innovation has been at the heart of Miele's success for over 100 years

From the first fully automatic washing machine to the latest energy and water saving technology, we lead the way. When you buy a Miele machine you benefit from innovative, intelligent solutions that deliver reliable results.

Our drive to innovate is independently recognized too we've won awards for everything from design through to the way we apply technology. When we design a new machine we think about how we can make it better - the details we can change to improve performance, increase efficiency and deliver the best results.

Innovation doesn't end with our products either - we're always looking at ways to improve the service we give to our customers, listening to you and being responsive to ensure that we're delivering the products you need.





Shortest programme cycle (secs)

Dishwashing programmes

Gillman's Support & Service

Gillman's has a team of 16 expert engineers to support customers, with an aim to complete all repairs within 24 hours.

All Engineers are Gas Safe registered and fully trained and accredited by Miele to install, commission and service the equipment that they supply.

The team of experienced staff are able to carry out detailed site surveys free of charge and can recommend power supplies (including gas), drainage, water supply and also check water pressure if required

Miele PROFESSIONAL Gillman's



Sustainable, cost effective performance

Because you don't want to worry about the impact of rising energy prices, we have developed all of our products to lead the market for energy and water efficiency. At the heart of all our product design is sustainable, cost-effective performance that achieves optimum results.

Our machines last longer too, so you will replace them less often, minimising environmental impact and disposal costs. When a product does come to the end of its life, most of it is easily recyclable - so from start to finish we are ensuring maximum sustainability.

Our machines offer many characteristics which significantly contribute to sustainability: low consumption (of energy, water and chemical substances), a high proportion of recyclable materials and secondary raw materials and environmentally friendly procedures.

In addition, all European company locations are certified to ISO 9001, ISO14001, OHSAS 18001 and SA 8000 standards.

57%

lower CO₂ emissions since 2000

2,860,000

Wh energy saving per year at our new office in Gütersloh

2004

Miele has been a member of the UN Global Compact an initiative promoting sustainability in businesses since 2004 Our machines last longer, so you will replace them less often, minimising environmental impact and disposal costs.



Miele's global reputation for reliability is no accident.

All our products undergo meticulous testing to simulate over ten years of continuous and rigorous use.

At Miele we are renowned for the build quality of our range and we rigorously endurance test all of our products during their development. When we say rigorously we really do mean it, for example our laundry products are tested to run for up to 30,000 hours - that is a lot of clean sheets, towels or mop heads.

Every product we manufacture goes through an endof-line test too, before passing quality control; we pay attention to the details so that you don't have to.

We are committed to our products, response times, deliveries and installs being correct first time. All of this means machines that deliver outstanding reliability, long product lifecycles and low running costs. An investment in Miele results in long-term cost savings and peace of mind.

Miele Professional. Immer Besser

Miele Quality Pledges



Our washing machines are tested to

30,000 cycles

that's the equivalent of 8 cycles a day, 7 days a week for over 10 years



The doors on our **dishwashers** are opened and closed

00,000 times



The on/off switch on our washing machines and tumble dryers is tested to operate

100,000 times



The doors on our washing machines are opened, closed, locked and unlocked

60,000 times



Our **tumble dryers** are tested to

40,000 cvcles



The detergent dispenser flap on our **washing machines** is opened and closed

30,000 times



All our PM range ironers are tested to operate for up to

20,000 hours



Our **dishwashers** are tested to

12,000 cycles



The fluff flap on our **tumble dryers** is opened and closed

10,000 times



All our **tumble dryers'** central bearing and support rollers operate for more than

20,000 hours

Miele



Gillman's St Oswalds Road, Gloucester, Gloucestershire, GL1 2SG



f @gillmansappliances